

DIGITAL AC/DC CLAMP METER MS2160



Specifications		MS2160
Specifications	Range	Accuracy
DC Voltage	4V/40V/400V/600V	±(0.8%+3)
AC Voltage	4V/40V/400V/600V	±(1.0%+3)
DC Current	4A/40A/80A	±(2.5%+5)
AC Current	4A/40A/80A	±(2.5%+5)
Resistance	400Ω/4KΩ/40KΩ/400KΩ/4MΩ	±(0.8%+3)
	40MΩ	±(1.2%+3)
A position(Clamp)	99.99Hz/999.9Hz/>1kHz	±(1.5%+5)
V position	99.99Hz/999.9Hz/9.999kHz/>10kHz	±(1.5%+5)
Capacitance	4/40/400nF/4/40/400uF/4/40mF	±(4.0%+3)
Temperature	-20°C~1000°C	±(3.0%+3)
	-4°F~1832°F	
Duty Cycle	0.5%~99.5%	±3.0%
Features		
Display	counts	4000
Jaw Size		Φ24mm/1.0"
Auto Ranging	Auto & Manual	●
APO	Auto Power Off	●
NCV	Non-Contact Voltage Detector	●
Diode	2.5V	●
Continuity	<50Ω	●
Data Hold		●
Display Backlight		●
Work Light		●
LBD	Low Battery Display	●
Power Supply	1x1.5V AAA Battery	
Product Size	195mmx80mmx45mm/7.8"x3.1"x1.8"	
Product Weight	195g/0.43lb	
Safety Rating	CE ETL CAT III 600V RoHS	



MS2160

JAW SIZE
Φ24mm/1.0"

VOLTAGE AC 600V
DC 600V

CURRENT AC 80A
DC 80A

